

Coaxial Cable Connector 16_QMA-50-4-1/133_N

Description

Right angle cable plug

Interface standards
QMA QLF compliant



Technical Data

Electrical Data

Impedance	50 Ω			
Interface frequency max.	18 GHz			
Frequency range	DC to 2 GHz	2 to 3 GHz		3 to 5 GHz
Return loss	30 dB	28 dB		25 dB

Mechanical Data

Centre contact	soldered
Outer contact	crimped
Weight	0.0075 kg

Environmental Data

Operating temperature	-40 °C to 85 °C
2011/65/EU, RoHS	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Bronze	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00007705
Catalogue drawing	DOU-00007707
Assembly instruction	DOC-0000182579

Ordering Information

Bulk 100 pcs package	16_QMA-50-4-1/133_NH
----------------------	----------------------

Additional Information

Suitable cables	S_04262_D, LL141
-----------------	------------------