

Coaxial Cable Connector 24_BMA-N50-2-21/11-_N

Description

Straight panel bulkhead cable jack, flange mount

Interface standards

IEC 60169-33_MIL-STD-348/321 fully intermateable

Technical Data

Electrical Data

| | |
|--------------------------|--------|
| Impedance | 50 Ω |
| Interface frequency max. | 18 GHz |

Mechanical Data

| | |
|----------------|-------------|
| Centre contact | soldered |
| Outer contact | crimped |
| Weight | 0.003657 kg |

Environmental Data

| | |
|--|------------------|
| Operating temperature | -65 °C to 125 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|--|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Copper Beryllium Alloy | Gold Plating (without Nickel underplating) |
| Body | Stainless Steel | |
| Insulator | PFA / PTFE | |
| Crimp ferrule | Copper | Nickel Plating |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00130826 |
| Assembly instruction | DOC-0000453588 |
| Mounting hole | DOU-00008950 |

Ordering Information

| | |
|----------------|------------------------|
| Single package | 24_BMA-N50-2-21/11-_NE |
|----------------|------------------------|

Additional Information

| | |
|-----------------|-----------|
| Suitable cables | RG_316_/U |
|-----------------|-----------|