

Coaxial Cable Connector 24_BMA-N50-3-18/11-_N

Description

Straight bulkhead cable feed through

Interface standards

IEC 60169-33_MIL-STD-348/321 fully intermateable



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 18 GHz |

Mechanical Data

| | |
|----------------|------------|
| Centre contact | plugged |
| Outer contact | soldered |
| Weight | 0.00301 kg |

Environmental Data

| | |
|--|------------------|
| Operating temperature | -65 °C to 125 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|--|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Copper Beryllium Alloy | Gold Plating (without Nickel underplating) |
| Body | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Insulator | PFA / PTFE | |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00130554 |
| Assembly instruction | DOC-0000453501 |
| Mounting hole | DOU-00008950 |

Ordering Information

| | |
|----------------|------------------------|
| Single package | 24_BMA-N50-3-18/11-_NE |
|----------------|------------------------|

Additional Information

| | |
|-----------------|---------------|
| Suitable cables | EZ_141_TP_M17 |
|-----------------|---------------|