

Coaxial Cable Connector 25_BMA-N50-3-10/113_N

Description

Straight panel cable jack, flange mount

Interface standards

IEC 60169-33_MIL-STD-348/321 fully intermateable



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	12.4 GHz

Mechanical Data

Centre contact	plugged
Outer contact	soldered

Environmental Data

Operating temperature	-40 °C to 125 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Copper Beryllium Alloy	SUCOPRO Plating
Body	Brass	SUCOPLATE (R) Plating
Other body part	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00228609
Catalogue drawing	DCA-00009940
Assembly instruction	DOC-0000406844
Mounting hole	DOU-00008816

Ordering Information

Bulk 100 pcs package	25_BMA-N50-3-10/113_NH
----------------------	------------------------

Additional Information

Suitable cables	EZ_141_TP_M17, SUCOFORM_141, MULTIFLEX_141
-----------------	--