

EMP Protector 3403.17.0051

Description

Fine protector hybrid technology

Benefits

DC continuity for remote powering
Broad-band design
Replaceable GDT 9071.99.0548, (90 V) included
Compliant to IEC 61643-21



Product Configuration

Main path connectors Port 1: unprotected, N plug (male) - Port 2: protected, N jack (female)
Mounting and grounding M6 (screw), brk (bracket)

Technical Data

Electrical Data

Impedance 50 Ω
Frequency range 806 - 2500 MHz
Return loss ≥ 20.8 dB
Insertion loss ≤ 0.5 dB
RF CW power ≤ 50 W
PIM 3rd order not specified

DC supply voltage ≤ 15 V
DC current ≤ 3 A
Surge current handling capability 30 single / 20 multiple kA (test pulse 8/20 μ s)
Residual pulse energy 6 μ J typically (test pulse 4 kV 1.2/50 μ s / 2 kA 8/20 μ s) main path - protected side

Mechanical Data

Number of matings 500
Weight 330 g

Environmental Data

Operating temperature -40 °C to +85 °C
Waterproof degree IP65 (according to IEC 60529, data refer to the coupled state)
2011/65/EU (RoHS - including compliant acc. Annex III
2015/863 and 2017/2102)

Material Data

Piece Parts	Material	Surface Plating
Housing	Aluminium	Chromatized
Port 1 center contact	Brass	Gold Plating (without Nickel underplating)
Port 2 center contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)

Related Documents

Outline drawing DOU-00018513.1
Mounting instruction DOC-0000176104

Remarks

Residual pulse amplitude: typ. <100V (test pulse 10 kV, 5/200 ns)
Residual pulse amplitude: typ. <50V (test pulse 6 kV, 5/200 ns)
Measured with capsuel 9071.99.0548, 90 V acc. MIL-STD-461
Recommendation: if this protector is mated with connectors made of copper-alloy base material and trimetal or nickel plating the connector area must be taped to improve long-term durability.

EMP Protector 3403.17.0051