Data Sheet



Coaxial PCB Connector 86_CT-0-2-2/111_N

Description

Right angle PCB cable terminator

Interface Standards



Technical Data

Electrical Data

Impedance other Ω

Mechanical Data

Board mounting type through holes Weight 0.0031 kg

Environmental Data

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102) -65 °C to 165 °C compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing DOU-00012693
Catalogue drawing DCA-00012695
Assembly instruction DOC-0000192791

Ordering Information

Single package 86_CT-0-2-2/111_NE

Remarks

PCB connector without stand-offs, suitable for cable group U2 (RG 316/U), cable entry: crimped

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.