

3-Way Power Splitter K7431348

Reactive Splitter

Description

Installation Equipment for Sencity Special Communication Antennas:
3-Way Power Splitter 380-512 MHz
For indoor and outdoor use



Technical Data

Electrical Data

	Signal Band 1		
Frequency	0.38 - 0.512 GHz		
Insertion Loss	0.05 dB		
Max. Composite Power	1000 W		
	Input 1		
Connector Type	7/16		
Connector Gender	jack (female)		
	Output 1	Output 2	Output 3
Connector Type	7/16	7/16	7/16
Connector Gender	jack (female)	jack (female)	jack (female)
Char. impedance	50 Ω		

VSWR < 1.1

Mechanical Data

Dimensions 409 x 82 x 82 mm (Height x Width x Length)

Packing size (mm): 425 x 93 x 107

Environmental Data

Environmental conditions indoor/outdoor
2011/65/EU (RoHS - including compliant
2015/863 and 2017/2102)
WEEE 2002/96/EC no special marking needed

Material:

Case: Aluminum

Inner conductor: Brass

Mounting:

Bracket for wall mounting included in the scope of supply. For mounting to tubular masts use clamps as listed below (order separately).

Related Products

734364 Tension Band 120-140mm

Related Documents

Mounting instruction DOC-0000871752

3-Way Power Splitter K7431348

Security instruction
Outline drawing

DOC-0000278984
DOU-00397212