


ELECTRICAL SPECIFICATIONS

SPECIFICATIONS	SPECIFICATIONS		UNIT
Frequency Range	2400 ~ 2500	5150 ~ 5850	MHz
Gain	3.0	5.0	dBi
VSWR (in Center Frequency), max	2.0		-
Return Loss, max	-10		dBi
Impedance	50		Ω
Operating Temperature Range	-40 ~ +80		°C
Storage Temperature Range	-40 ~ +85		°C
Antenna Material	FPC		
Connector	IPEX		-
Cable Diameter	1.37		mm




DIMENSIONS




Unit: mm

FREQUENCY CHARACTERISTICS (S11)

Trc3 S11 SWR 1 U / Ref 1 U



■ EFFICIENCY AND PEAK GAIN



Frequency (MHz)	2400	2450	2500	5150	5350	5550	5750	5850
Gain (dBi)	3.2	2.84	2.74	3.98	4.16	5.32	5.11	4.28
Efficiency (%)	61.9	62.4	61.4	66.3	63.9	65.6	68.9	69.7

May, 2017

Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.