





📴 Share



I Email

Feedback

What can we help you find?

Products

Industries

Resources

About TE

My Account

Innovation

Support Center

Home > Products > RF & Coax > Product Feature Selector > Product Details

1-1337473-0 Product Details



Pricing & Availability Request Sample Add to My Part List

Buy Product through

Distributor

🗎 Print

- Connector RF
- Plug
- Applies To Coaxial Cable
- Without Snap-Lock

Related Products Not quite the product you're looking for? **Find Similar Products View Part in Product** Feature Selector Check for Tooling

	Coaxial Cable Termin	ation Type = Solder/Clamp	
ocuments	Compliance		
Please Note: Use the Product Drawing for all	l design activity		
Product Type Features		Contact Features	
Product Type ?	Connector - RF	Center Contact Plating	Silver
Gender ?	Plug	Contact Base Material	Brass
Dielectric Material 🔋	PTFE		
Coupling Nut Style 🔋	Knurled	Configuration Features	
Rubber Gasket ?	With	Snap-Lock	Without
Grade	Professional		141A, 58C, Raychem 5021D1331, Raychem
Coupling Nut Material	Brass	Coaxial Cable Type (RG/U or Mfg.) ?	5021D1831, Raychem 5021M1631, Raychem
Sealed	No	(Kd/0 01 1 lig./ =	EPD 71169Q, URM 43, URM 76
Isolated	No		
Flats Dimension	11.0 A/F	Industry Standards	
Mechanical Attachment	t	RoHS/ELV Compliance	RoHS compliant, ELV compliant
Panel Mount Retention	Without	Lead Free Solder Processes ?	Not relevant for lead free process
Electrical Characteristi	ics	RoHS/ELV Compliance History	Converted to comply with RoHS directive
Impedance Options	Non-Constant		
		Environmental	

lats Dimension	11.0 A/F
Mechanical Attachment	:
Panel Mount Retention	Without
Electrical Characteristi	cs
Impedance Options	Non-Constant
Termination Features	
Coaxial Cable Termination Type	Solder/Clamp
Body Features	
Body Size ?	Standard
Body Plating 🛽	Silver
Body Style	Straight
Body Material	Brass
Polarized	No
Gasket Material	White Silicone Rubber

RoHS/ELV Compliance	RoHS compliant, ELV compliant	
Lead Free Solder Processes ?	Not relevant for lead free process	
RoHS/ELV Compliance History	Converted to comply with RoHS directive	
Environmental		
Operating Temperature (Max.) (°C)	165	
Conditions for Usage		
Applies To ?	Coaxial Cable	
Packaging Features		
Packaging Method ?	Individual	
Packaging Quantity	25	
Other		
Brand	Greenpar	
VI 1 61 - 161 - 11		

Corporate Information

About TE Investors News Room Supplier Portal Careers

Terms & Conditions Privacy Policy Global Accessibility Statement

Quick Links Distributor Inventory

Product Cross Reference Documents & Drawings Product Compliance Support Center Site Map

Email or Chat With Us Find a Phone Number Knowledge Base Manage Your Account

Customer Support

UHF Connectors

Node Classification

Keep Me Informed







