

RF CONNECTORS



✓ Active

TE CONNECTIVITY (TE)

BNC Str Plg Hex 500hm Nickel Plated RG17

Miniature Coax | HMX , STA

1-1337534-0

TE Internal Number: 1-1337534-0

EU RoHS Compliant with Exemptions EU ELV Compliant with Exemptions

Connector Interface BNC

Connector Style Plug

Mated Outer Diameter (Approximate) 14.529 mm [.572 in]

Impedance (Ω) 50

Cable Type Raychem 5026A1318, Raychem 5026A1331, Raychem 5026A1631, Raychem 5026C1309, Raychem 5026D1028, Raychem 5026D1424, Raychem CLFH-316, Raychem EPD 26995Q, RG 174A, RG 188A, URM 95



DOCUMENTATION

Product Drawings

BNC STRAIGHT PLUG CRIMP 50 OHM RG174A/U, 188A/U, 316/U, URM95, KX3B, KX22A

PDF (TIFF AVAILABLE)

English

FEATURES



Please review product documents or contact us for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Interface BNC
Connector Style Plug
Sealable No
Connector & Contact Terminates To Wire & Cable
Configuration Features
Number of Positions 1
Electrical Characteristics
Impedance (Ω) 50
Body Features
Cable Connector Orientation Straight
Body Material Brass
Body Plating Material Nickel
Body Insulation With
Contact Features
Crimp Type Hex
Center Contact Plating Material Gold
Center Contact Material Brass
Termination Features
Termination Method to Wire & Cable Crimp
Dimensions
Mated Outer Diameter (Approximate) 14.529 mm [.572 in]
Usage Conditions
Cable Type Raychem 5026A1318, Raychem 5026A1331, Raychem 5026A1631, Raychem 5026C1309, Raychem 5026D1028, Raychem 5026C1309, Raychem 5026D1028, Ra
5026D1424, Raychem CLFH-316, Raychem EPD 26995Q, RG 174A, RG 188A, URM 95
Operation/Application
Operating Frequency (GHz) 4
Packaging Features
Packaging Method Box
Packaging Quantity 50
Other
Dielectric Material PTFE
Gasket Material Silicone Rubber
Coupling Nut Material Brass
Grade Professional

PRODUCT COMPLIANCE

Statement of Compliance

Statement of Compliance

PDF