

 [Live Product Chat](#)



✓ Active

 Add to Part List

 Always EU RoHS/ELV Compliant (Statement of Compliance)

- Connector
- Jack
- Connector Type = SMA
- Without Snap-Lock
- Terminate To Microstrip

[View all Features](#) | [Find Similar Products](#)

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)
- ▶ [Request Samples](#)

NEW!

- [OSM JACK MICROSTRIP TRANSITION](#) (PDF, English)

- None Available

- None Available

- None Available

- None Available

- None Available

- Product Line Information

- Tooling

List all Documents

- Product Type = Connector
- Gender = Jack
- Connector Type = SMA
- Body Style = Straight
- Number of Panel Mount Holes = 4
- Body Material = Stainless Steel
- Body Finish = Gold
- Center Contact = With
- Terminal Type = Tab
- Captivated Contacts = With
- Tab Width (mm [in]) = 0.51 [0.02]
- Dielectric Material = TFE Fluorocarbon
- Comment = Microstrip Transition

- Panel Attachment = With
- Panel Attachment Method = Flange
- Panel Attachment Style = Front Mount

- Impedance (Ω) = 50

- Snap-Lock = Without
- Length (mm [in]) = 15.24 [0.600]

- Center Contact Material = Beryllium Copper
- Center Contact Plating = Gold

- Government/Industry Qualification = No
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

- Terminate To = Microstrip

- Brand = AMP