



CONNECTORS

RF CONNECTORS



✓ Active

TE CONNECTIVITY (TE)

3052 1648 10

Standard Coax

1057293-1

TE Internal Number: 1057293-1

Alias ID: 3052-1648-10

EU RoHS Compliant with Exemptions

EU ELV Compliant with Exemptions

Connector Interface N Type

Connector Style Jack

Mated Outer Diameter (Approximate) 19.05 mm [.75 in]

Impedance (Ω) 50

Operating Frequency (GHz) 10

[↓ PRODUCT DRAWING](#)
English

[↓ 3D PDF](#)

DOCUMENTATION

Product Drawings

OSN FLANGE MOUNT JACK RECEPTACLE TAB TERMINAL

PDF (TIFF AVAILABLE)

English

CAD Files

3D PDF

PDF

3D

Customer View Model

2D_DXF.ZIP

English

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Interface N Type

Connector Style Jack

Connector & Contact Terminates To Printed Circuit Board

Configuration Features

PCB Mounting Orientation Vertical

Electrical Characteristics

Impedance (Ω) 50

Body Features

Body Material Brass

Body Plating Material Nickel over Copper

Contact Features

Center Contact Plating Material Gold over Copper

Center Contact Material Beryllium Copper

RF Connector Contact Configuration Not Captivated

Termination Features

Termination Method to PC Board Through Hole - Solder

Mechanical Attachment

Panel Mount Retention Type Square Flange

Panel Attachment Style Front Mount

Dimensions

Mated Outer Diameter (Approximate) 19.05 mm [.75 in]

Operation/Application

Operating Frequency (GHz) 10

Packaging Features

Packaging Method Carton

Other

Dielectric Material TFE Fluorocarbon

Grade Commercial

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF
