

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



 Active

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

- ? Connector
- ? Plug
- ? Coaxial Cable Termination Type = MIL - Clamp
- ? Terminate To Coaxial Cable
- ? Coaxial Cable Type (RG/U or Mfg.) = 214, 9B, Raychem 5012A3422, Raychem 5012F3332, Raychem 5012F3832, Raychem 5012M3612, URM 91

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

- ? [TYPE-N STRAIGHT PLUG SOLDER 50 OHM RG9B/U, 214/U, U...](#)
(PDF, English)

? None Available

? None Available

? None Available

? None Available

? None Available

? Product Line Information

? Tooling

List all Documents

Product Type Features:

- ? Product Type = Connector
- ? Gender = Plug
- ? Body Style = Straight
- ? Grade = Commercial
- ? Lightning/EMP Protection = None
- ? Dielectric Material = PTFE
- ? Weatherproof = No
- ? Flats Dimension = 15.8 A/F
- ? Body Material = Brass
- ? Gasket Material = White Silicone Rubber
- ? Coupling Nut Material = Brass

? Panel Attachment = Without

- ? Frequency = DC - 11 GHz
- ? Connector Impedance (?) = 50

? Coaxial Cable Termination Type = MIL - Clamp

? Body Plating = Silver

? Center Contact Plating = Silver

? Center Contact Material = Brass

? Captured Center Contact = With

? Coaxial Cable Type (RG/U or Mfg.) = 214, 9B,
Raychem 5012A3422, Raychem 5012F3332,
Raychem 5012F3832, Raychem 5012M3612,
URM 91

- ? Government/Industry Qualification = No
- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Converted to comply with RoHS directive

? Terminate To = Coaxial Cable
? Operating Temperature (Max.) (°C) = 165
? Military Style Number = UG -21D/U

- ? Packaging Method = Individual
- ? Packaging Quantity = 50

? Brand = Greenpar