

 [Live Product Chat](#)



✓ Active

 [Add to Part List](#)

 Converted to EU RoHS/ELV Compliant (Statement of Compliance)

- Connector
- Plug
- Connector Type = SMA
- Without Snap-Lock
- Terminate To Coaxial Cable

[View all Features](#) | [Find Similar Products](#)

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)
- ▶ [Request Samples](#)

NEW!

Product Drawings:

- [SMA RIGHT ANGLE CRIMP ATTACHMENT CAPTIVE CONTACT RG...](#) (PDF, English)

- None Available

- None Available

- None Available

- None Available

- None Available

Additional Information:

- Product Line Information

Related Products:

- Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- Gender = Plug
- Connector Type = SMA
- Crimp Type = Hex
- Body Style = Right Angle
- Body Material = Stainless Steel
- Body Finish = Gold
- Center Contact = With
- Retractable Collar = Without
- Safety Wire Holes = Without
- Grade = Professional
- Dielectric Material = PTFE
- Coupling Nut Material = Stainless Steel
- Coupling Nut Finish = Gold
- Gasket Material = Silicone Rubber
- Retaining Ring Material = Stainless Steel
- Sealed = No
- Isolated = No
- Flats Dimension = 8.0 A/F

Mechanical Attachment:

- Panel Attachment = Without

Electrical Characteristics:

- Impedance (Ω) = 50
- Frequency = DC - 12.4 GHz

Termination Related Features:

- Coaxial Cable Termination Type = Solder/Crimp

Body Related Features:

- Snap-Lock = Without
- Length (mm [in]) = 12.60 [0.496]
- Ferrule Material = Brass
- Ferrule Plating = Gold
- Polarized = No
- Hexcrimp Dimension = 0.65 Sq + 2.8 + 3.4

Contact Related Features:

- Center Contact Material = Brass
- Center Contact Plating = Gold

Configuration Related Features:

- Coaxial Cable Type (RG/U or Mfg.) = 174A, 188A, 316, KX 22A, KX 3B, URM 95

Industry Standards:

- Government/Industry Qualification = No
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

- Terminate To = Coaxial Cable
- Operating Temperature (Max.) (°C) = 165

Packaging Related Features:

- Packaging Quantity = 100

Other:

- Brand = Greenpar