



+ CONNECTORS  
RF CONNECTORS



✓ Active

TE CONNECTIVITY (TE)  
SERIES N JACK W/PROOF  
Standard Coax

225089-4  
TE Internal Number: 225089-4

Not EU RoHS Compliant  
Not EU ELV Compliant

Connector Interface N Type  
Connector Style Jack  
Mated Outer Diameter (Approximate) 19.05 mm [ .75 in ]  
Impedance (Ω) 50  
Cable Type RG 225

↓ PRODUCT DRAWING  
English

DOCUMENTATION

Product Drawings

JACK,PANEL,WEATHERPROOF, SERIES N  
PDF (TIFF AVAILABLE)  
English

Instruction Sheets

Instruction Sheet (U.S.)

AMP\* COAXICON\* 50 OHM, R.F. CONNECTORS SERIES N PANEL JACKS  
PDF  
English

AMP\* COAXICON\* 50 OHM, R.F. CONNECTORS SERIES N PANEL JACKS  
TIF  
English

Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

- Connector Interface N Type
- Connector Style Jack
- Connector & Contact Terminates To Wire & Cable

Electrical Characteristics

- Impedance (Ω) 50

Body Features

- Cable Connector Orientation Straight
- Body Material Brass
- Body Plating Material Silver

Contact Features

- Crimp Type Dual
- Center Contact Plating Material Gold
- Center Contact Material Beryllium Copper
- RF Connector Contact Configuration Not Captivated

Termination Features

- Termination Method to Wire & Cable Crimp

Mechanical Attachment

- Panel Mount Retention Type Flange
- Panel Attachment Style Rear Mount

Dimensions

- Mated Outer Diameter (Approximate) 19.05 mm [ .75 in ]

Usage Conditions

- Cable Type RG 225

Packaging Features

- Packaging Method Carton

Other

- Dielectric Material Fluoropolymer
- Grade Military

Statement of Compliance

**Statement of Compliance**

PDF