

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

? Header
? Header Type = Breakaway
? Number of Rows = Dual
? Number of Positions = 4
? Mating Post Length = 5.84 mm

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

? None Available

? None Available

? None Available

? None Available

? None Available

? None Available

? Product Line Information

? Tooling

? Product Type = Header

? Number of Positions = 4

? Mount Angle = Vertical

? PCB Retention Feature = No

? Surface Mount Compatible = No

? Board Standoff = Without

? Mounting Ears = Without

? Mating Connector Lock = Without

? Post Size (mm [in]) = 0.64 [.025]

? Comment = Headers may be broken to desired number of positions using Hand Tool No. 91406 -1, or Tool Kit No. 314818 -1. Other tail lengths are available, consult Tyco Electronics.

? Panel Attachment = Without

? Termination (Solder) Post Length (mm [in]) = 3.05 [0.120]

? Solder Tail Contact Plating = Tin over Nickel, Matte Tin over Nickel

? Header Type = Breakaway

? Number of Rows = Dual

? Centerline, Matrix (mm [in]) = 2.54 x 2.54
[.100 x .100]

? Selectively Loaded = No

? Mount Type = PC Board

? Contact Mating Area Plating = Gold (5)
 ? Contact Shape = Square
 ? Contact Material = Phosphor Bronze

?	Housing Material = Liquid Crystal Polymer (LCP)	
?	Housing Flammability Rating = UL 94V	-0

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin in - Paste capable to 245°C, Pin in - Paste capable to 260°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? High Temperature Housing = Yes

? High Speed Serial Data Connector = No

? Brand = AMP