



+ CONNECTORS
RF CONNECTORS



✓ Active

TE CONNECTIVITY (TE)
PLUG, COML BNC, KIT
Miniature Coax | [KT](#) , [KTT](#)

7-227079-2
TE Internal Number: 7-227079-2

Not EU RoHS Compliant
Not EU ELV Compliant

Connector Interface BNC
Connector Style Plug
Mated Outer Diameter (Approximate) 14.529 mm [.572 in]
Impedance (Ω) 50
Cable Type Belden 9209, Belden 9291, RG 59, RG 59A, RG 59B, RG 62, RG 62A, RG 62B

 **PRODUCT DRAWING**
English

 **3D PDF**

DOCUMENTATION

Product Drawings
PLUG, COMMERCIAL, BNC
PDF
English

CAD Files
3D PDF
PDF
English

Customer View Model
2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Instruction Sheets

Instruction Sheet (U.S.)

COAXICON BNC 50-Ohm RF Series Commercial Plug Connectors (Dual Crimp) 227079-[]

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

- Connector Interface BNC
- Connector Style Plug
- Sealable No
- Connector & Contact Terminates To Wire & Cable

Configuration Features

- Number of Positions 1

Electrical Characteristics

- Impedance (Ω) 50

Body Features

- Cable Connector Orientation Straight
- Body Material Brass
- Body Plating Material Nickel over Copper
- Body Insulation Without

Contact Features

- Crimp Type Dual
- Center Contact Plating Material Silver over Copper
- Center Contact Material Brass
- Center Contact Plating Thickness (μin) 7620

Termination Features

- Termination Method to Wire & Cable Crimp

Dimensions

Mated Outer Diameter (Approximate) 14.529 mm [.572 in]

Usage Conditions

Cable Type Belden 9209, Belden 9291, RG 59, RG 59A, RG 59B, RG 62, RG 62A, RG 62B

Packaging Features

Packaging Method Box

Other

Dielectric Material Polyethylene

Coupling Nut Material Brass

Grade Commercial

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF