



Search by part # or keyword 

Products

Industries & Solutions

Resources

Shop TE


Sign In



[Connectors](#) > [RF & Coax Connectors](#) > [RF Adapters](#) > [Between Series Adapters](#)

1046243-1

Between Series Adapters, Side A Interface BNC, Side A Gender Jack, Side B Interface SMA, Side B Gender Plug, 50 Ω , Cable-to-Cable, 1 Position



AMP

TE Internal #: **1046243-1**

TE Internal Description: **ADAPTER, BNC JACK TO SMA PLUG**

Alias #: **1250-1200-00**

Side A Interface : **BNC**

Side A Gender : **Jack**

Side B Interface : **SMA**

Side B Gender : **Plug**

Impedance (Ω): **50**

 [Digital Datasheet](#)

[Compatible Parts & Tooling](#)

Purchase items directly from TE.com

We are here to help!

Get in touch with our product experts.



[CHAT WITH US](#)



[EMAIL US](#)



[CALL US](#)

Documents

Features

Product Compliance

Product Drawings

[BNC JACK TO OSM PLUG ADAPTER](#)

tif English

[ADAPTER, BNC JACK TO SMA PLUG](#)

 [ADAPTER, BNC JACK TO SMA PLUG](#)

English

CAD Files

3D PDF

 [3D_CVM_CVM_1046243-1_D.pdf](#)

3D

Customer View Model

 [ENG_CVM_CVM_1046243-1_D.2d_dxf.zip](#)

English

 [ENG_CVM_CVM_1046243-1_D.3d_igs.zip](#)

English

 [ENG_CVM_CVM_1046243-1_D.3d_stp.zip](#)

English

Datasheets & Catalog Pages

Products for Aerospace and Defense

 [ENG_DS_1308940_Aerospace_Defense_0118.pdf](#)

English

Feedback



Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.	
Product Type Features	Side A Interface : BNC Side A Gender : Jack Side B Interface : SMA Side B Gender : Plug Connector System : Cable-to-Cable Connector & Contact Terminates To : Wire & Cable
Configuration Features	Number of Positions : 1
Electrical Characteristics	Impedance (Ω): 50
Body Features	Body Plating Material : Nickel Body Style : Straight Body Material : Brass
Contact Features	RF Connector Center Contact Material : Beryllium Copper RF Connector Center Contact Plating Material : Gold
Mechanical Attachment	Connector Mounting Type : Cable Mount (Free-Hanging) Coupling Nut Material : Stainless Steel
Usage Conditions	Operating Temperature Range : -65 – 125 °C [-85 – 257 °F]
Operation/Application	Circuit Application : Signal
Other	Dielectric Material : TFE Fluorocarbon Gasket Material : Silicone Rubber Coupling Nut Plating Finish : Passivated
Statement of Compliance	Statement of Compliance pdf

