

SCI-3513-000 PRODUCT DATASHEET

Resin Sealed Bolt-in Filters

[Home](#)

SCI-3513-000 Product Specifications

Circuit Type	Pi
Lead Diameter (in)	0.05
Lead End Style	HOOK
Working Voltage	100
Current (A)	25
Capacitance (pF)	100000
Capacitance MIN (pF)	100000
DC Resistance (Ohms, Max)	0.01
IL @ 1MHz (dB)	10
IL @ 10MHz (dB)	28
IL @ 30MHz (dB)	37
IL @ 100MHz (dB)	70
IL @ 300MHz (dB)	70
IL @ 1GHz (dB)	70
IL @ 10GHz (dB)	70
Oper. Temp MIN (C)	-55
Oper. Temp MAX (C)	125

Resin Sealed Bolt-in Filters

View Sales Drawing

Request a Quote

Request a Sample

Consult an Engineer

Check Distribution Inventory



Contact Electromagnetic Integrated Solutions

8061 Avonia Road
Fairview, PA 16415
P: +1 (814) 474 1571
F: +1 (814) 474 3110

Visit Our Other API Technologies Sites

- RF2M

RF/Microwave & Microelectronics
- EIS

Electromagnetic Integrated Solutions
- POWER

Power Solutions
- SSIA

Secure Systems & Information Assurance
- EMS

Electronics Manufacturing Services

Get in Touch

- [Contact Us](#) >
- [Request a Quote](#) >
- [Consult an Engineer](#) >

Learn More

- [About Us](#) >
- [Press Releases](#) >
- [Compliance Testing](#) >
- [EMC Testing](#) >
- [Manufacturing Facilities](#) >
- [Low-Cost Manufacturing](#) >
- [Trade Shows & Events](#) >
- [Career Opportunities](#) >

Resources

- [Find Sales Reps](#) >
- [Distributor Network](#) >
- [Partners Login](#) >
- [Stock Check](#) >
- [Quality Certifications](#) >

Products

- [Coaxial Filters & Interconnects](#) >
- [Power Filters & Film Capacitors](#) >
- [Advanced Ceramics](#) >
- [Magnetics](#) >
- [Custom Cable & Harnessing](#) >
- [Specialty Connectors & Cabling](#) >

Engineering Tools

- [Technical Information](#) >
- [10 Commandments](#) >
- [Project Starter](#) >

Follow Us

- [Follow us on Twitter](#) >
- [Join us on LinkedIn](#) >
- [Like us on Facebook](#) >
- [Google+ Community](#) >
- [Blog](#) >